ADITI PLAIN 69-Silk collection

NB: The portrayed colours may differ from reality.

69-2421 SALT

69-2422 WOOL

69-2423 CHAMPAGNE

69-2424 RHINO


69-2425 RAFFIA

69-2426 MOCHA

69-2427 BOULDER

69-2428 OLIVE

69-2429 BLACK PEPPER

Specification

Name	Aditi Plain	
Width approx.	110 cm - 43”	
Weight approx.	gr / lm oz / lnyd	: 215 : 6.9
Thickness	approx. 0.47 mm	
Composition	silk linen	: 42% : 58%
Weaving technique	jacquard woven	
Dyeing	yarn dyed	
Backing	reinforced woodpulp recycled polyester	: 70% : 30%
Repeat approx.	height width	: - : -
Hanging	random, non-reverse	

Scan QR-code for more details, visuals and video content.

Performance	Please contact info@tapetex.com for more detailed test reports.
Surface finish	A stain repellent finish prevents waterbased splashes penetrating and staining the material. Periodic vacuuming is recommended to prevent dust from building up on the materials surface.
Lightfastness	Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.
LRV values	Testing as per BS 8493:2008+A1:2010, Datacolor DC500.
Fire rating	ASTM E84 Class 1 or A and EUROCLASS (B s1 d0).
Permeability rating	Test result 63.7 as per ASTM E96-12, Method B, Water Vapor Transmission.
Indoor air quality	ASTM D6196, D5197 and D5116, Environmental Chamber Test. The testing followed UL 2821 "Greenguard Certification Program Method for Measuring and Evaluating Chemical Emissions".
REACH SVHC	Compliant as per Centexbel testing.

Treated with a stain repellent finish

Lightfastness: as per ISO 105-B02:2014 Xenotest

Light reflection: as per BS 8493: 2008+A1:2010 Datacolor DC500

Fire resistant: EU: B, s1-d0 US: ASTM E84 Class 1 or A

Permeability rating: 63.7, as per ASTM E96-12 Method B



Indoor air quality: ASTM D6196, D5197 and D5116

Sustainability
Silk is a 100% renewable natural resource. The backing is FSC certified, FSC A000531.
In production, all energy sources are either green, wind or hydro based and all processes are waterbased. The products do not contain PVC, chlorine, plasticizers, heavy metals or harmful dyes.

Supply and packing
Delivery from stock by the full linear meter or full linear yard. The average piece length of this quality is approx. 50 linear meter or 55 linear yards. However, as is common within the textile industry, it is not possible to establish a standard roll length. The wallcovering is reeled on to a cardboard core, wrapped in polyethylene and protective end caps are fixed. Each roll is then packed in individual cardboard boxes or tubes, which are also made out of FSC certified woodpulp.

Harmonized System as per the World Customs Organization and Origin
Textile Wallcovering, paper backed: 5905.00. Made in the Netherlands.

CE EN 15102

REACH

FSC Forest Stewardship Council, Certification FSC A000531.

Carbon Neutral Shipping

PVC FREE

100% BIO BASED

Hanging details

Hanging	Random, non-reverse. Precision trimmed for butt-joining by professional paper hangers. Installation advice supplied with every roll. Use rubber roller instead of spatula. Direction of hanging is printed on back of wallcovering.
Adhesive	Use a premixed heavy duty, clear vinyl adhesive, suitable for textile wallcovering.
Variation	There can be a variation between sample material and finished product. Stock cuttings are available for approval.



Precision trimmed | Sold by the meter/yard | Direction of hanging | Use a rubber roller | Don't use a spatula | Apply adhesive on the wall

View



Aditi Plain 69-2425