

Tapetex PRO-1 Wallcovering Adhesive

E.031708.v1

General properties

Tapetex PRO-1 is a commercial grade wallcovering adhesive designed for contractors. The adhesive is suitable for the installation of any light to heavy weight textile and vinyl wallcovering with a nonwoven, paper or fabric backing. It has excellent wet adhesion and a generous open time. Tapetex PRO-1 also features a bactericide and mildewcide for in-can protection.

Specification data

Adhesive type	: Starch and resin dispersion-based adhesive
Percent solids	: Approx. 28%
Color	: White
Open time	: 15 - 45 Minutes
Bonding time	: 1 - 4 Hours
Consumption	: Approx. 5m ² per kilo
Packing	: 10 kg oval buckets
Storage	: In a closed packing at room temperature; frost-resistant up to -10°C
Shelf life	: In a closed packing 12 months

Surface preparation

The surface must be free from grease and other residues. It should also be dry, smooth, structurally sound and normally absorbent. Check the surface for paint bonding, loose wallcovering, damaged plaster, etc. If the surface is too absorbent or if it has a powdery surface you may pre-paste with the adhesive diluted with 20% water to stabilize it.

Application method

Tapetex PRO-1 is ready to use. Apply a thin even coat of adhesive on the substrate using a lambs-wool roller or paintbrush. The open time and bonding will vary depending on the temperature, ventilation and humidity of the room.

Cleaning

Avoid getting adhesive on the surface of the material, especially textile wallcovering. If this happens remove the adhesive immediately when still wet with a damp sponge and dry the wallcovering with a clean dry towel.

Warranty

Tapetex warrants that it will replace this product free of charge if, within 12 months of delivery, it is found to be defective in material or workmanship. The remedy is limited to the replacement of the product and Tapetex disclaims all liability for consequential, punitive and special damages. Conditions of use are beyond our control.

Safety

Keep out of reach of children. Not for human consumption. Only use in well ventilated areas. In case of ingestion seek medical attention immediately. If contact with eyes occurs, flush with water for 15 minutes. In any doubt consult a doctor. Do not mix with other chemical products.



Material Safety Data Sheet of Tapetex PRO-1 Wallcovering Adhesive

1.1	Product	Tapetex PRO-1 Wallcovering Adhesive
1.2	Supplier	Tapetex BV, Churchillaan 10, 5705 BK Helmond - Holland T +31(0)492 534 690, info@tapetex.com, www.tapetex.com
1.3	Emergencies	See under 4.
2.	Hazard identification	Non-hazardous material according to EU criteria.
3.	Chemical composition	Paste based on starch and synthetic resin dispersion.
4.	First-Aid measures	
4.1	Contact with eyes	Rinse with cold running water. When in doubt seek medical advice.
4.2	Contact with skin	Contact may cause skin irritation. Clean thoroughly with water.
4.3	Swallowing	When product is swallowed, immediately seek medical advice.
5.	Fire-fighting measures	
5.1	General	Product does not burn. Use extinguishing measures appropriate to the surroundings of the fire.
5.2	Extinguishing media	Dry powder, CO ₂ , sand, water.
6.	Measures when product is released	
6.1	General	Absorb product with absorbing material and dispose of according to local regulations. Avoid contamination of sewerage or public waters. Preferably clean with cleaning agent; avoid use of solvents. When the product has contaminated public waters or sewerage, inform authorities in accordance to local regulations.
7.	Handling and storage	
7.1	General	No special safety measures required.
7.2	Handling	Observe safety and health regulations in your working area.
7.3	Storage	Protect against frost; store at room temperatures between 5°C and 30°C in dry and ventilated area, protect against heat sources and avoid direct sunlight. Always store product in closed buckets.
8.	Exposure and personal protection equipment	
8.1	General safety	General ventilation is required.
8.2	Respiratory protection	No special measures required.
8.3	Skin protection	Skin cream can be used for protection only before contact with product has occurred. After skin contact clean with water.
8.4	Eye protection	Use safety eyeglasses when splashing may be expected.

9. Physical and chemical properties

9.1 Appearance	liquid, broken white colour
9.2 Odour	slightly acid
9.3 Boiling point	100°C (water)
9.4 Flash point	not applicable
9.5 Solubility in water	completely miscible

10. Stability and reactivity

The product is stable when handled and stored in accordance to the description given in this bulletin (standard industrial practice).

11. Toxicological information

Product is non-toxic. According to our information the product will not cause health risks when handled and stored in accordance to standard industrial practices.

12. Ecological information

No data known concerning the product itself. According to our information the product will not cause environmental risks when handled and stored in accordance to standard industrial practices.

13. Disposal considerations

Avoid contamination of sewerage or public waters. Dispose of according to local regulations.

14. Transportation

The product is non-hazardous with regard to transportation.

15. Regulatory information

No data required according to EEG regulations.

16. Other information

The information given in this Material Safety Data Sheet is based on our present knowledge.
Application and working circumstances are not known to the authors of this bulletin and therefore cannot be influenced by them.
Without prior written application instructions, this product is not suitable for any other application as described in paragraph 1. The end-user is always and solely responsible for the arrangement of required measures with regard to local regulations.